

usignolo



Volt 230/50 1-ph

usignolo dry



Volt 230/50 1-ph

	I-Gal	HP	I./min.-CFM	Bar-Psi	dB/A	cm AxBxC inch.	Kg - Lbs	cm AxBxC inch.	Kg - Lbs	dryer				
usignolo	24-6,34	1	100-3,57	62-2,21	8-116	70	45x45x65	18x18x26	28-62	55x55x65	22x22x26	40-88	no	1
usignolo dry	24-6,34	1	100-3,57	62-2,21	8-116	70	45x60x70	18x24x28	38-84	85x70x100	33x28x39	50-110	yes	1

(*) @ 5 bar (73PSI)

rondine



Volt 230/50 1-ph
220/60 1-ph
115/60 1-ph

rondine dry



Volt 230/50 1-ph
220/60 1-ph
115/60 1-ph

	I-Gal	HP	I./min.-CFM	Bar-Psi	dB/A	cm AxBxC inch.	Kg - Lbs	cm AxBxC inch.	Kg - Lbs	dryer				
rondine	24-6,34	2	155-5,54	121-4,32	8-116	72	45x47x65	18x19x26	31-68	55x55x65	22x22x26	45-99	no	1
rondine dry	24-6,34	2	155-5,54	121-4,32	8-116	72	45x60x70	18x24x28	41-90	85x70x100	33x28x39	55-121	yes	1